

# ROTARY-ONLY MULTIPLE-CUTTER BITS

## NON-REMOVABLE-SHANK, MULTIPLE CUTTER BITS

### CONCRETE-TERMITE®, SOLID BODY STYLE



DIAMETER POINT	DIAMETER SHANK	OVERALL LENGTH	DRILLING DEPTH	PART NO.	LIST PRICE	WT. (lbs)	RECOMMENDED RPM
3/16"	3/16"	4"	2 3/16"	TD-3-4	\$ 9.00	0.1	550-900
1/4"	1/4"	5"	3"	TD-4-5	17.00	0.1	550-900
5/16"	1/4"	5"	3"	TD-5-5	19.00	0.1	550-900
3/8"	5/16"	5"	3"	TD-6-5	23.00	0.1	550-900
3/8"	5/16"	8"	6"	TD-6-8	30.00	0.3	550-900
7/16"	5/16"	5"	3"	TD-7-5	33.00	0.3	550-900
1/2"	3/8"	8"	5"	TD-8-8	34.00	0.4	450-750
1/2"	3/8"	18"	14 1/2"	TD-8-18	41.00	0.8	450-750
9/16"	3/8"	8"	4 1/2"	TD-9-8	41.00	0.4	450-750

### CONCRETE-TERMITE, CORE STYLE



DIAMETER POINT	DIAMETER SHANK	OVERALL LENGTH	DRILLING DEPTH	PART NO.	LIST PRICE	WT. (lbs)	SUGGESTED RPM
5/8"	1/2"	8"	4 1/2"	TD-10-8	\$ 42.00	0.5	450-750
3/4"	1/2"	8"	4 1/2"	TD-12-8	52.00	0.6	450-750

## E-Z STARTER POINTS for TD CORE BITS



Used to help keep the core bit from "skipping" across the masonry when first contact is made. The E-Z in-and-out design is quick and simple to use.

PART NO.	WILL FIT THESE CORE BIT DIAMETERS	LIST PRICE	WT. (lbs)
SP-10	5/8"	\$ 14.00	0.1
SP-12	3/4"	14.00	0.1
SP-14	7/8"	15.00	0.1
SP-16	1"	16.00	0.1
SP-18	1 1/8"	17.00	0.1
SP-20	1 1/4"	20.00	0.2
SP-22	1 3/8" thru 1 5/8"	21.00	0.2
SP-28	1 3/4" thru 2 1/4"	26.00	0.2
SP-40	2 1/2" thru 3"	44.00	0.6

## REMOVABLE-SHANK CORE BITS



### CORE BODY - 4 1/2" OAL, 3 1/2" Core Depth

DIAMETER	TD CORE BIT COMPLETE - 9" OAL			TD CORE BIT HEAD ONLY			SUGG. RPM	SHANKS FOR TD CORE BITS HEAD ONLY PART NO.	SHANK DIA.	TO MAKE OVERALL BIT LENGTH	LIST PRICE	WT. (lbs)	THREAD SIZE
	PART NO.	LIST PRICE	WT. (lbs)	PART NO.	LIST PRICE	WT. (lbs)							
7/8"	TD-14-9	\$69.00	0.8	TD-14HO	\$ 58.00	0.4	350-750	TDS-2-9 (Supplied w/ complete bit)	1/2"	9"	\$11.00	0.4	1/2 - 13
1"	TD-16-9	76.00	0.9	TD-16HO	66.00	0.5	350-750						
1 1/8"	TD-18-9	82.00	1.1	TD-18HO	72.00	0.7	350-750						
1 1/4"	TD-20-9	91.00	1.1	TD-20HO	80.00	0.7	350-750						
1 3/8"	TD-22-9	97.00	1.3	TD-22HO	87.00	0.9	350-750						
1 1/2"	TD-24-9	103.00	1.4	TD-24HO	93.00	1.0	350-750						
1 5/8"	TD-26-9	111.00	1.4	TD-26HO	100.00	1.0	350-750						
1 3/4"	TD-28-9	118.00	1.6	TD-28HO	108.00	1.2	350-750	TDS-2-12 TDS-2-18 TDS-2-24	1/2"	12"	13.00	0.5	
2"	TD-32-9	131.00	2.2	TD-32HO	120.00	1.5	250-450						
2 1/4"	TD-36-9	165.00	2.8	TD-36HO	155.00	2.1	250-450						
2 1/2"	TD-40-9	180.00	3.1	TD-40HO	170.00	2.4	250-450						
3"	TD-48-9	228.00	3.7	TD-48HO	218.00	3.0	250-450	TDS-3-9 (Supplied w/ complete bit)	1/2"	9"	\$11.00	0.4	3/4 - 10
								TDS-3-12 TDS-3-18 TDS-3-24	1/2"	12"	13.00	0.5	3/4 - 10

## DIAMOND DRILL RIG ADAPTORS



PART NO.	WILL FIT THESE RELTON PRODUCTS	THREAD SIZE	LIST PRICE	WT. (lbs)
1258	3/4" - 7/8" Hole Saws, 7/8" - 1 3/4" TD Core Bits & Rebar Eaters	1/2-13 to 5/8-11	\$ 12.00	0.3
3458	1" - 4" Hole Saws, 2" & up TD Core Bits & Rebar Eaters	3/4-10 to 5/8-11	12.00	0.4
34114	1" - 4" Hole Saws, 2" & up TD Core Bits & Rebar Eaters	3/4-10 to 1 1/4-7	18.00	0.4

Adapt our core bits, Rebar Eaters and hole saws for use on diamond drill rigs... May be used wet or dry cut.