

NFPA  Health Fire Reactivity	 MATERIAL SAFETY DATA SHEET Meets requirements of 29 CFR 1910.1200 (Federal Hazard Communication Standard)	HMS <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>Health</td><td style="text-align: center;">1</td></tr> <tr><td>Fire</td><td style="text-align: center;">1</td></tr> <tr><td>Reactivity</td><td style="text-align: center;">1</td></tr> </table>	Health	1	Fire	1	Reactivity	1
Health	1							
Fire	1							
Reactivity	1							

SECTION I

MANUFACTURER'S NAME: RELTON CORPORATION 317 ROLYN PLACE ARCADIA, CA 91007-2838 EMERGENCY RESPONSE for spill, leak, exposure, etc: Chemtrec - (800) 424-9300 For non-emergency product information: Relton Corp - (323) 681-2551 (800) 423-1505	PRODUCT NAME OR NUMBER: NEW Rapid Tap® CHEMICAL NAME & SYNONYMS: Predominantly Chlorinated Paraffin CHEMICAL FAMILY: Chlorinated Paraffin FORMULA: Mixture (see Section II)
--	--

SECTION II COMPONENTS

	TLV	PEL	STEL	C.A.S. NO.	% wt.
Paraffin, chlorinated	NE	NE	NE	61788-76-9	< 40
Mineral Oil	5 mg/m ³	5 mg/m ³	NE	64742-58-1	< 50
Metal-Cutting-Fluid Additive	5 mg/m ³	10 mg/m ³	NE	Trade secret	< 8
Soybean Oil, epoxidized	NE	NE	NE	8013-07-8	> 1
Olefin Sulfide	5 mg/m ³	5 mg/m ³	NE	Trade secret	< 1
Cinnamon Oil Perfume	NE	NE	NE	-- --	trace

SECTION III - PHYSICAL DATA

Data is based upon testing mixture as a whole.

BOILING POINT (X°F) (C°):	450° F	SPECIFIC GRAVITY (H ₂ O=1) @ 25° C:	1.02	Freezing Point:	-20° F
VAPOR PRESSURE (mm Hg):	NF	PERCENT VOLATILE BY VOLUME (%):	NA	VOC: Negligible	
VAPOR DENSITY (AIR=1):	NF	EVAPORATION RATE (WATER=1): Slower than water			
SOLUBILITY IN WATER:	< .2%	pH: NA			
APPEARANCE AND ODOR: light amber color; slight, sweet odor			MATERIAL IS LIQUID		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Data is based upon testing mixture as a whole.

FLASH POINT (method used): 350° F COC	FLAMMABLE LIMITS: Non-Flammable	LFL	UFL
		ND	ND
EXTINGUISHING MEDIA: Carbon Dioxide, Foam, Dry Chemical, Water, Fog			
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus with full facepiece in a pressure-demand mode; full-body protective clothing. Treat as oil fire			
UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustion can produce acid gases (hydrogen chloride, hydrogen sulfide) Exposing containers to intense heat could cause drums to rupture. Cool fire-exposed containers with water spray to prevent rupture			

SECTION V - HEALTH HAZARD DATA

ROUTES OF ENTRY & SYMPTOMS OF OVEREXPOSURE: Eyes and skin: may cause mild irritation. Inhalation: may cause mild upper respiratory irritation. Ingestion: possible nausea.
EMERGENCY AND FIRST AID PROCEDURES: Eyes: flush for 15 min. with water. Skin: wash with soap and water. Inhalation: remove to fresh air. Ingestion: do not induce vomiting; give lots of water to a conscious person. Call Doctor

